NSN 5305-01-192-0681

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-192-0681 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.595 inches and 0.625 inches **Fastener Length:** Between 4.060 inches and 4.070 inches **Head Style:** Hexagon **Head Height:** Between 0.490 inches and 0.500 inches Width Between Flats: Between 0.552 inches and 0.561 inches **Shoulder Diameter:** 0.490 inches first shoulder and 0.500 inches first shoulder **Shoulder Length:** 3.420 inches first shoulder and 3.450 inches first shoulder **Internal Drive Style:** Hexagon **Thread Diameter:** 0.375 inches Width Across Flats: 0.250 inches Thready Qty Per Inch (tpi): 16 Hardness Rating: 31.0 rockwell c **Shoulder Shape:** Round first shoulder Material: Steel comp 4130 **Material Specification:** Qq-s-626 federal specification single material response **Surface Treatment:** Zinc and chromate **Surface Treatment Specification:** Qq-z-325, ty2, cl2 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

NSN 5305-01-192-0681

Shoulder Screw - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A003b0