NSN 5305-01-192-1429

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-192-1429 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.552 inches and 0.592 inches **Fastener Length:** Between 4.124 inches and 4.144 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 1.170 inches and 1.190 inches **Head Height:** Between 0.300 inches and 0.320 inches **Grip Diameter:** Between 0.7485 inches and 0.7490 inches **Shank Unthreaded Hole Diameter:** 0.141 inches first hole and 0.146 inches first hole **Internal Drive Style:** High-torque **Thread Diameter:** 0.750 inches **Grip Length:** Between 3.552 inches and 3.572 inches Thready Qty Per Inch (tpi): 16 Distance From Head Largest Bearing Surface To Shank Hole Center: 3.999 inches first hole and 4.029 inches first hole Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-01-192-1429

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0