NSN 5305-01-192-1429

Close Tolerance Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-192-1429



Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.552 inches and 0.592 inches
Fastener Length:
Between 4.124 inches and 4.144 inches
Head Style:
Pan no. 2
Head Diameter:
Between 1.170 inches and 1.190 inches
Head Height:
Between 0.300 inches and 0.320 inches
Grip Diameter:
Between 0.7485 inches and 0.7490 inches
Shank Unthreaded Hole Diameter:
0.141 inches first hole and 0.146 inches first hole
Internal Drive Style:
High-torque
Thread Diameter:
0.750 inches
Grip Length:
Between 3.552 inches and 3.572 inches
Thready Qty Per Inch (tpi):
16
Distance From Head Largest Bearing Surface To Shank Hole Center:
3.999 inches first hole and 4.029 inches first hole
Material:
Steel comp xm-13
Material Specification:
Ams 5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

- ---

NSN 5305-01-192-1429

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

