## NSN 5305-01-192-2208

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-192-2208 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.490 inches and 0.510 inches **Fastener Length:** Between 1.240 inches and 1.250 inches **Head Style:** Flat chamfer **Head Diameter:** 0.940 inches **Head Height:** 0.630 inches **First Diameter From Head:** Between 0.460 inches and 0.470 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.740 inches and 0.750 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.625 inches Width Across Flats: 0.500 inches Thready Qty Per Inch (tpi): 11 **Criticality Code Justification: Externally Relieved Body Diameter Quantity:** Material: Stainless steel **Thread Series Designator:** Unc **Reference Number Differentiating Characteristics:** Material will be in accordance with ships parts control center activity hx quailty control, manufacturing and testing specifications Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5305-01-192-2208

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0