Assembled Washer Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-192-3340



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.293 inches and 0.375 inches Fastener Length: Between 0.343 inches and 0.375 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.078 inches and 0.080 inches Washer Quantity: 2 **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 55000 pounds per square inch Hardness Rating: 45.0 rockwell c secondary washer and 53.0 rockwell c secondary washer Secondary Washer Relationship To Primary Washer: Not identical Secondary Washer Style: Flat **Primary Washer Outside Diameter:** 0.172 inches Secondary Washer Outside Diameter: Between 0.213 inches and 0.223 inches **Primary Washer Style:** Split helical ring Primary Washer Material Thickness: 0.025 inches **Secondary Washer Material Thickness:** Between 0.013 inches and 0.019 inches Material: Steel

NSN 5305-01-192-3340

Assembled Washer Screw - Page 2 of 2



Material Specification:

Qq-s-633 federal specification single material response fastener

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl2 federal specification single treatment response

Thread Series Designator:

Unc

Specification Data:

80205-nas1301 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0