## NSN 5305-01-192-3742

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-192-3742 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.875 inches **Fastener Length:** 1.125 inches **Head Style:** Fillister **Head Diameter:** Between 0.292 inches and 0.313 inches **Head Height:** Between 0.123 inches and 0.130 inches **First Diameter From Head:** 0.144 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.800 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 8630 **Material Specification:** Mil-s-6050 military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

## NSN 5305-01-192-3742

Externally Relieved Body Screw - Page 2 of 2



U	ni	t	O:	F	м	e	а	s	u	r	e	:
_	• • •	•	_	•	•••	_	•	_	•	•	•	•

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6050 spec.