## NSN 5305-01-192-5735



Socket Head Cap Screw - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-01-192-5735 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.199 inches and 0.250 inches **Fastener Length:** Between 0.230 inches and 0.250 inches **Head Style:** Watertight **Head Diameter:** Between 0.256 inches and 0.294 inches **Head Height:** Between 0.087 inches and 0.097 inches **Locking Feature:** Strip threads or patch threads or pellet threads **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Special Features:** Furnished with one silicone o-ring Material: Steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7 **Material Specification:** Qq-s-763 federal specification 1st material response or astm a493 assn standard 1st material response or qq-s-763 federal specification 2nd material response or astm a493 assn standard 2nd material response or qq-s-763 federal specification 3rd material response or astm a493 assn standard 3rd material response or astm a493 assn standard 4th material response or astm a493 assn standard 5th material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

Fiig:

No

Demilitarization: