

View Online at <https://aerobasegroup.com/nsn/5305-01-192-5735>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.199 inches and 0.250 inches

**Fastener Length:**

Between 0.230 inches and 0.250 inches

**Head Style:**

Watertight

**Head Diameter:**

Between 0.256 inches and 0.294 inches

**Head Height:**

Between 0.087 inches and 0.097 inches

**Locking Feature:**

Strip threads or patch threads or pellet threads

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.138 inches

**Thready Qty Per Inch (tpi):**

32

**Special Features:**

Furnished with one silicone o-ring

**Material:**

Steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7

**Material Specification:**

Qq-s-763 federal specification 1st material response or astm a493 assn standard 1st material response or qq-s-763 federal specification 2nd material response or astm a493 assn standard 2nd material response or qq-s-763 federal specification 3rd material response or astm a493 assn standard 3rd material response or astm a493 assn standard 4th material response or astm a493 assn standard 5th material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0