NSN 5305-01-192-9299

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-192-9299

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.308 inches and 0.375 inches |
| Fastener Length: |
| Between 1.068 inches and 1.115 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.339 inches and 0.381 inches |
| Grip Diameter: |
| Between 0.1885 inches and 0.1895 inches |
| Internal Drive Style: |
| Offset cruciform (torque set) |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 0.740 inches and 0.760 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 220000 pounds per square inch |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Surface Finish: |
| 32.0 microinches threads |
| Product Name: |
| Navy special project |
| Special Features: |
| Internal drive ribbed |
| Material: |
| Steel comp h11 |
| Material Specification: |
| Ams 6487 assn standard single material response |
| Surface Treatment: |
| Cadmium or cadmium and chromate |
| Surface Treatment Specification: |
| Nas 672 assn standard 1st treatment response or mil-c-8837, type 2, cl 2 military specification 2nd treatment response |
| Thread Series Designator: |

Unjf

NSN 5305-01-192-9299

Close Tolerance Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.

