## NSN 5305-01-193-1486

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-193-1486 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.186 inches **Fastener Length:** 0.312 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.195 inches and 0.225 inches First Diameter From Head: Between 0.078 inches and 0.088 inches **Second Diameter From Head:** 0.112 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.059 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.245 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Externally Relieved Body Diameter Quantity:** Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** Fed standard 66 federal standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response

Unc

**Thread Series Designator:** 

## NSN 5305-01-193-1486

Externally Relieved Body Screw - Page 2 of 2



She	lf	I if	ρ.
~	•••		•

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0