NSN 5305-01-193-1905

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-193-1905 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.615 inches and 0.682 inches **Fastener Length:** Between 1.187 inches and 1.234 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.7556 inches and 0.7604 inches **Head Height:** Between 0.1147 inches and 0.1167 inches **Grip Diameter:** Between 0.3740 inches and 0.3745 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.375 inches **Grip Length:** Between 0.552 inches and 0.572 inches Thready Qty Per Inch (tpi): 24 **Countersink Angle:** 100.0 degrees **Surface Finish:** 32.0 microinches threads **Special Features:** Cetyl alcohol lubrication, furnished with o ring Material: Titanium alloy **Material Specification:** Ams 4967, comp 6al-4v assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-01-193-1905

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0