## NSN 5305-01-193-2361

Machine Screw - Page 1 of 1

No Fiig: A500d0



View Online at https://aerobasegroup.com/nsn/5305-01-193-2361 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.534 inches and 0.558 inches **Fastener Length:** Between 0.578 inches and 0.608 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.096 inches and 0.119 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.060 inches Thready Qty Per Inch (tpi): 80 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385 **Screw Material Specification:** Qq-s-763 federal specification single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:**