NSN 5305-01-193-2386

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-193-2386

| View Online at https://aerobasegroup.com/nsn/5305-01-193-2386 |
|--|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.650 inches and 0.700 inches |
| Fastener Length: |
| Between 1.035 inches and 1.065 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.6047 inches and 0.6741 inches |
| Grip Diameter: |
| Between 0.4360 inches and 0.4370 inches |
| Internal Drive Style: |
| High-torque |
| Thread Diameter: |
| 0.438 inches |
| Grip Length: |
| Between 0.365 inches and 0.385 inches |
| Thready Qty Per Inch (tpi): |
| 20 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Surface Finish: |
| 32.0 microinches threads |
| Product Name: |
| Navy special project |
| Material: |
| Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416, ty2 cl2 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| • |
| 80205-nas1581 professional/industrial association standard |
| • |

N/a

NSN 5305-01-193-2386

Close Tolerance Screw - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A003b0