

View Online at <https://aerobasegroup.com/nsn/5305-01-193-2387>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.352 inches and 0.403 inches

Fastener Length:

Between 3.414 inches and 3.434 inches

Head Style:

Crowned hexagon

Head Height:

Between 0.189 inches and 0.204 inches

Width Between Flats:

Between 0.553 inches and 0.564 inches

Locking Feature:

Detent ball grip

Grip Diameter:

Between 0.3737 inches and 0.3742 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.116 inches first hole

Internal Drive Style:

Slot

Thread Diameter:

0.375 inches

Grip Length:

Between 2.875 inches and 2.891 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

63000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.286 inches first hole and 3.306 inches first hole

Surface Finish:

32.0 microinches grip

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0