

View Online at <https://aerobasegroup.com/nsn/5305-01-193-6838>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.442 inches and 0.500 inches

Fastener Length:

Between 0.470 inches and 0.500 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.112 inches and 0.118 inches

Head Height:

Between 0.070 inches and 0.073 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.073 inches

Width Across Flats:

Between 0.063 inches and 0.064 inches

Thready Qty Per Inch (tpi):

72

Min. Tensile Strength (psi):

80000 pounds per square inch

Hardness Rating:

80.0 rockwell b

Minimum Yield Strength:

30000 pounds per square inch

Material:

Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp xm-7 or steel comp 384

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unrf

Specification Data:

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0