## NSN 5305-01-193-6847

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-193-6847 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.353 inches and 0.388 inches **Fastener Length:** Between 1.551 inches and 1.566 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.360 inches and 0.374 inches **Head Height:** Between 0.115 inches and 0.125 inches **Grip Diameter:** Between 0.1890 inches and 0.1895 inches **Shank Unthreaded Hole Diameter:** 0.070 inches first hole and 0.080 inches first hole **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches **Grip Length:** Between 1.178 inches and 1.198 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 1.410 inches first hole and 1.460 inches first hole **Surface Finish:** 32.0 microinches threads **Product Name:** Navy special project Material: Titanium alloy **Material Specification:** Ams 4967 comp 6al-4v assn standard single material response **Thread Series Designator:** Unjf

Ch.

Shelf Life:

N/a

## NSN 5305-01-193-6847

Close Tolerance Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0