## NSN 5305-01-193-6850

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-193-6850

Thread Classe
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.251 inches and 0.301 inches
Fastener Length:
Between 1.261 inches and 1.291 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.376 inches and 0.385 inches
Grip Diameter:
Between 0.1890 inches and 0.1895 inches
Shank Unthreaded Hole Diameter:
0.070 inches first hole and 0.075 inches first hole
Internal Drive Style:
High-torque
Thread Diameter:
0.190 inches
Grip Length:
Between 0.990 inches and 1.010 inches
Thready Qty Per Inch (tpi):
32
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Distance From Head Largest Bearing Surface To Shank Hole Center:
1.148 inches first hole and 1.168 inches first hole
Material:
Steel comp xm-13
Material Specification:
Ams 5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

## NSN 5305-01-193-6850

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

