

View Online at <https://aerobasegroup.com/nsn/5305-01-193-9698>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.312 inches

**Fastener Length:**

Between 0.897 inches and 0.927 inches

**Head Style:**

Flat countersunk undercut

**Head Diameter:**

0.531 inches

**Head Height:**

Between 0.057 inches and 0.059 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Countersink Angle:**

100.0 degrees

**Screw Material:**

Steel

**Screw Surface Treatment:**

Cadmium and chromate

**Screw Surface Treatment Specification:**

Qq-p-416 type 2 class 2 federal specification single treatment response

**Special Features:**

Concentric hole in head 0.1596 in. Min dia, 0.1675 in. Maximum diameter 0.190 in. Thd dia, 32 threads per in. Jf class 3b, countersunk 90 degrees, 0.156 in. Min dia, 0.187 in. Maximum dia; 0.310 in. Min length, 0.507 in. Length

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0