NSN 5305-01-193-9698

Machine Screw - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-193-9698

| view Online at https:/ | //aerobasegroup.com/nsn/5305-01-193-9698 |
|------------------------|--|
| Thread Class: | |
| 3a | |
| Thread Direction: | |
| Right-hand | |
| Thread Length: | |
| 0.312 inches | |
| Fastener Length: | |
| Between 0.897 inche | s and 0.927 inches |
| Head Style: | |
| Flat countersunk und | ercut |
| Head Diameter: | |
| 0.531 inches | |
| Head Height: | |
| Between 0.057 inche | s and 0.059 inches |
| nternal Drive Style: | |
| Slot | |
| Thread Diameter: | |
| 0.250 inches | |
| Thready Qty Per Inc | h (tpi): |
| 28 | |
| Min. Tensile Strengt | th (psi): |
| 160000 pounds per s | quare inch |
| ountersink Angle: | |
| 00.0 degrees | |
| Screw Material: | |
| Steel | |
| Screw Surface Trea | tment: |
| Cadmium and chrom | ate |
| Screw Surface Trea | tment Specification: |
| Qq-p-416 type 2 clas | s 2 federal specification single treatment response |
| Special Features: | |
| Concentric hole in he | ad 0.1596 in. Min dia, 0.1675 in. Maximum diameter 0.190 in. Thd dia, 32 threads per in. Jf class 3b, countersunk 90 |
| degrees, 0.156 in. Mi | n dia, 0.187 in. Maximum dia; 0.310 in. Min length, 0.507 in. Length |
| Thread Series Desig | jnator: |
| Unjf | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| - | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A500d0 | |