

View Online at <https://aerobasegroup.com/nsn/5305-01-194-0593>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.650 inches and 2.000 inches

Fastener Length:

Between 1.900 inches and 2.000 inches

Head Style:

Flat chamfer

Head Diameter:

Between 1.479 inches and 1.500 inches

Head Height:

Between 0.988 inches and 1.000 inches

Locking Feature:

Strip threads

Internal Drive Style:

Hexagon

Thread Diameter:

1.000 inches

Width Across Flats:

Between 0.750 inches and 0.757 inches

Thready Qty Per Inch (tpi):

8

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

38.0 rockwell c and 45.0 rockwell c

Minimum Yield Strength:

130000 pounds per square inch

Chamfer Angle:

Between 30.0 degrees and 45.0 degrees

Material:

Steel fastener

Surface Treatment:

Oxide fastener

Surface Treatment Specification:

Mil-c-13924, class 3 military specification single treatment response fastener

Thread Series Designator:

Unrc

Specification Data:

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.