NSN 5305-01-194-0642

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-194-0642

Thread Class:	
Ba	
Thread Direction:	
Right-hand	
Fhread Length:	
Between 0.378 inches and 0.428 inches	
Fastener Length:	
Between 0.950 inches and 0.980 inches	
lead Style:	
Pan no. 2	
lead Diameter:	
Between 0.477 inches and 0.492 inches	
lead Height:	
Between 0.140 inches and 0.150 inches	
Grip Diameter:	
Between 0.2485 inches and 0.2495 inches	
nternal Drive Style:	
High-torque	
Thread Diameter:	
0.250 inches	
Grip Length:	
Between 0.552 inches and 0.572 inches	
Thready Qty Per Inch (tpi):	
28	
/in. Tensile Strength (psi):	
60000 pounds per square inch	
Surface Finish:	
32.0 microinches threads	
Material:	
ron alloy 660	
Material Specification:	
Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standa	ard single
naterial response	
Surface Treatment:	
Passivate	
Surface Treatment Specification:	
Qq-p-35 federal specification single treatment response	
Thread Series Designator:	
Jnjf	
Specification Data:	
30205-nas1578 professional/industrial association standard	
Shelf Life:	

N/a

NSN 5305-01-194-0642

Close Tolerance Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

