## NSN 5305-01-194-2983

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-194-2983 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.149 inches **Fastener Length:** 0.550 inches **Head Style:** Flat chamfer **Head Diameter:** 0.187 inches **Head Height:** 0.080 inches **First Diameter From Head:** 0.086 inches **Second Diameter From Head:** 0.116 inches **Third Diameter From Head:** 0.067 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.286 inches and 0.306 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.336 inches and 0.346 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 0.401 inches Point Style: Flat **Internal Drive Style:** Slot **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): 56 **Externally Relieved Body Diameter Quantity:** 3 Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response

Surface Treatment:

**Passivate** 

## NSN 5305-01-194-2983

Externally Relieved Body Screw - Page 2 of 2



Qq-p-35 type 4 federal specification single treatment response

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0