## NSN 5305-01-194-2994

Socket Head Cap Screw - Page 1 of 2





3aThread Direction:Right-handThread Length:Between 1.536 inches and 1.750 inchesFastener Length:Between 1.690 inches and 1.750 inchesHead Style:Flat chamferHead Diameter:Between 0.735 inches and 0.750 inchesHead Height:Between 0.492 inches and 0.500 inchesLocking Feature:Patch threadsInternal Drive Style:HexagonThread Diameter:0.500 inchesWith Across Flats:Between 0.375 inches and 0.379 inchesThready Cty Per Inch (tpi):13Min. Tensile Strength (psi):170000 pounds per square inchHardinesMinimum Yield Strength:15000 pounds per square inchMaterial:SteelStreatSteelSurface Treatment:Cadmium and chromate	Thread Class:
Right-handRight-handThread Length:Between 1.536 inches and 1.750 inchesFastener Length:Between 1.690 inches and 1.750 inchesHead Style:Flat chamferHead Diameter:Between 0.735 inches and 0.750 inchesHead Height:Between 0.492 inches and 0.500 inchesLocking Feature:Patch threadsInternal Drive Style:HexagonThread Diameter:0.500 inchesWidth Across Flats:Between 0.375 inches and 0.379 inchesThready Qty Per Inch (tpi):13Min. Tensile Strength (psi):170000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:150000 pounds per square inchMaterial:SteelStrelSteelSurface Treatment:	3a
Tread Length:Between 1.536 inches and 1.750 inchesFastener Length:Between 1.690 inches and 1.750 inchesHead Style:Flat chamferHead Diameter:Between 0.735 inches and 0.750 inchesHead Height:Between 0.492 inches and 0.500 inchesLocking Feature:Patch threadsInternal Drive Style:HexagonThread Diameter:0.500 inchesWidth Across Flats:Between 0.375 inches and 0.379 inchesThready Qty Per Inch (tpi):13Min. Tensile Strength (psi):170000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:150000 pounds per square inchMaterial:SteelSterel	Thread Direction:
Tread Length:Between 1.536 inches and 1.750 inchesFastener Length:Between 1.690 inches and 1.750 inchesHead Style:Flat chamferHead Diameter:Between 0.735 inches and 0.750 inchesHead Height:Between 0.492 inches and 0.500 inchesLocking Feature:Patch threadsInternal Drive Style:HexagonThread Diameter:0.500 inchesWidth Across Flats:Between 0.375 inches and 0.379 inchesThready Qty Per Inch (tpi):13Min. Tensile Strength (psi):170000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:150000 pounds per square inchMaterial:SteelSterel	Right-hand
Between 1.536 inches and 1.750 inchesFastener Length:Between 1.690 inches and 1.750 inchesHead Style:Flat chamferHead Diameter:Between 0.735 inches and 0.750 inchesHead Height:Between 0.492 inches and 0.500 inchesLocking Feature:Patch threadsInternal Drive Style:HexagonThread Diameter:0.500 inchesWidth Across Flats:Between 0.375 inches and 0.379 inchesThready Qty Per Inch (tpi):13Min. Tensile Strength (psi):170000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:150000 pounds per square inchMaterial:SteelSteelSurface Treatment:	-
Fastener Length:Between 1.690 inches and 1.750 inchesHead Style:Flat chamferHead Diameter:Between 0.735 inches and 0.750 inchesHead Height:Between 0.492 inches and 0.500 inchesLocking Feature:Patch threadsInternal Drive Style:HexagonThread Diameter:0.500 inchesWidth Across Flats:Between 0.375 inches and 0.379 inchesThready Qty Per Inch (tpi):13Min. Tensile Strength (psi):170000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:150000 pounds per square inchMaterial:SteelSteelSurface Treatment:	-
Between 1.690 inches and 1.750 inches Head Style: Flat chamfer Head Diameter: Between 0.735 inches and 0.750 inches Head Height: Between 0.492 inches and 0.500 inches Locking Feature: Patch threads Internal Drive Style: Hexagon Thread Diameter: 0.500 inches Width Across Flats: Between 0.375 inches and 0.379 inches Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 150000 pounds per square inch Material: Steel Steel	
Flat chamferHead Diameter:Between 0.735 inches and 0.750 inchesHead Height:Between 0.492 inches and 0.500 inchesLocking Feature:Patch threadsInternal Drive Style:HexagonThread Diameter:0.500 inchesWidth Across Flats:Between 0.375 inches and 0.379 inchesThready Qty Per Inch (tpi):13Min. Tensile Strength (psi):170000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:150000 pounds per square inchMaterial:SteelSteelSurface Treatment:	
Flat chamferHead Diameter:Between 0.735 inches and 0.750 inchesHead Height:Between 0.492 inches and 0.500 inchesLocking Feature:Patch threadsInternal Drive Style:HexagonThread Diameter:0.500 inchesWidth Across Flats:Between 0.375 inches and 0.379 inchesThready Qty Per Inch (tpi):13Min. Tensile Strength (psi):170000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:150000 pounds per square inchMaterial:SteelSteelSurface Treatment:	
Head Diameter:Between 0.735 inches and 0.750 inchesHead Height:Between 0.492 inches and 0.500 inchesLocking Feature:Patch threadsInternal Drive Style:HexagonThread Diameter:0.500 inchesWidth Across Flats:Between 0.375 inches and 0.379 inchesThready Qty Per Inch (tpi):13Min. Tensile Strength (psi):170000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:150000 pounds per square inchMaterial:SteelSteelSurface Treatment:	•
Between 0.735 inches and 0.750 inchesHead Height:Between 0.492 inches and 0.500 inchesLocking Feature:Patch threadsInternal Drive Style:HexagonThread Diameter:0.500 inchesWidth Across Flats:Between 0.375 inches and 0.379 inchesThready Qty Per Inch (tpi):13Min. Tensile Strength (psi):170000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:150000 pounds per square inchMaterial:SteelSteelSurface Treatment:	
Head Height:Between 0.492 inches and 0.500 inchesLocking Feature:Patch threadsInternal Drive Style:HexagonThread Diameter:0.500 inchesWidth Across Flats:Between 0.375 inches and 0.379 inchesThready Qty Per Inch (tpi):13Min. Tensile Strength (psi):170000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:150000 pounds per square inchMaterial:SteelSurface Treatment:	
Between 0.492 inches and 0.500 inchesLocking Feature:Patch threadsInternal Drive Style:HexagonThread Diameter:0.500 inchesWidth Across Flats:Between 0.375 inches and 0.379 inchesThready Qty Per Inch (tpi):13Min. Tensile Strength (psi):170000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:150000 pounds per square inchMaterial:SteelSteelSurface Treatment:	
Locking Feature:Patch threadsInternal Drive Style:HexagonThread Diameter:0.500 inchesWidth Across Flats:Between 0.375 inches and 0.379 inchesThready Qty Per Inch (tpi):13Min. Tensile Strength (psi):170000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:150000 pounds per square inchMaterial:SteelSteelSurface Treatment:	-
Patch threads Internal Drive Style: Hexagon Thread Diameter: 0.500 inches Width Across Flats: Between 0.375 inches and 0.379 inches Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 150000 pounds per square inch Material: Steel Steel	
Internal Drive Style:HexagonThread Diameter:0.500 inchesWidth Across Flats:Between 0.375 inches and 0.379 inchesThready Qty Per Inch (tpi):13Min. Tensile Strength (psi):170000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:150000 pounds per square inchMaterial:SteelSteelSurface Treatment:	
Hexagon Thread Diameter: 0.500 inches Width Across Flats: Between 0.375 inches and 0.379 inches Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 150000 pounds per square inch Material: Steel Surface Treatment:	
Thread Diameter:0.500 inchesWidth Across Flats:Between 0.375 inches and 0.379 inchesThready Qty Per Inch (tpi):13Min. Tensile Strength (psi):170000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:150000 pounds per square inchMaterial:SteelStrength:SteelStrength:SteelStrength:SteelStrength:SteelSte	
0.500 inches Width Across Flats: Between 0.375 inches and 0.379 inches Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating: 38.0 rockwell c_and 45.0 rockwell c Minimum Yield Strength: 150000 pounds per square inch Material: Steel Surface Treatment:	-
<ul> <li>Width Across Flats:</li> <li>Between 0.375 inches and 0.379 inches</li> <li>Thready Qty Per Inch (tpi):</li> <li>13</li> <li>Min. Tensile Strength (psi):</li> <li>170000 pounds per square inch</li> <li>Hardness Rating:</li> <li>38.0 rockwell c and 45.0 rockwell c</li> <li>Minimum Yield Strength:</li> <li>150000 pounds per square inch</li> <li>Material:</li> <li>Steel</li> <li>Surface Treatment:</li> </ul>	
Between 0.375 inches and 0.379 inches Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 150000 pounds per square inch Material: Steel Surface Treatment:	
Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 150000 pounds per square inch Material: Steel Surface Treatment:	
<ul> <li>13</li> <li>Min. Tensile Strength (psi):</li> <li>170000 pounds per square inch</li> <li>Hardness Rating:</li> <li>38.0 rockwell c and 45.0 rockwell c</li> <li>Minimum Yield Strength:</li> <li>150000 pounds per square inch</li> <li>Material:</li> <li>Steel</li> <li>Surface Treatment:</li> </ul>	
Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 150000 pounds per square inch Material: Steel Surface Treatment:	
170000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 150000 pounds per square inch Material: Steel Surface Treatment:	
Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 150000 pounds per square inch Material: Steel Surface Treatment:	
38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 150000 pounds per square inch Material: Steel Surface Treatment:	
Minimum Yield Strength: 150000 pounds per square inch Material: Steel Surface Treatment:	-
150000 pounds per square inch Material: Steel Surface Treatment:	
Material: Steel Surface Treatment:	_
Steel Surface Treatment:	
Surface Treatment:	
Cadmium and chromate	
Surface Treatment Specification:	
Qq-p-416, type 2, class 3 federal specification single treatment response	
Thread Carico Decignotor-	-
-	
Unc	
Unc Specification Or Standard:	6 type
Unc Specification Or Standard: 6 type	Shelf Life:
Unc Specification Or Standard: 6 type Shelf Life:	N/a
	Thread Series Designator:
inread Series Designator:	Unc
-	Specification Or Standard:
Unc	6 type
Unc Specification Or Standard:	Shelf Life:
Unc Specification Or Standard: 6 type	N/a
Unc Specification Or Standard: 6 type Shelf Life:	

## NSN 5305-01-194-2994

Socket Head Cap Screw - Page 2 of 2

AeroBase Group

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0