

View Online at <https://aerobasegroup.com/nsn/5305-01-194-3007>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.300 inches and 0.330 inches

Fastener Length:

Between 1.369 inches and 1.379 inches

Head Style:

Fillister

Head Diameter:

Between 0.250 inches and 0.270 inches

Head Height:

Between 0.086 inches and 0.096 inches

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Special Features:

Furnished with one lock washer; finish color black

Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

Surface Treatment:

Oxide

Surface Treatment Specification:

Mil-c-13924 military specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.