## NSN 5305-01-194-4874

Socket Head Cap Screw - Page 1 of 2



steel comp 384

View Online at https://aerobasegroup.com/nsn/5305-01-194-4874

Thr	ead Class:
3a	
Thr	ead Direction:
Rig	ht-hand
Thr	ead Length:
1.1	25 inches
Fas	stener Length:
Bet	ween 1.690 inches and 1.750 inches
Hea	ad Style:
Fla	countersunk
Неа	ad Diameter:
Bet	ween 1.112 inches and 1.188 inches
Inte	ernal Drive Style:
Hex	kagon
Thr	ead Diameter:
0.6	25 inches
Wio	th Across Flats:
0.3	75 inches
Thr	ready Qty Per Inch (tpi):
11	
Mir	a. Tensile Strength (psi):
800	00 pounds per square inch
Hai	dness Rating:
80.	0 rockwell b
Mir	imum Yield Strength:
300	00 pounds per square inch
Co	untersink Angle:
Bet	ween 80.0 degrees and 84.0 degrees
Ma	terial:
Ste	el comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 or s
Ma	terial Specification:
66	federal standard all material responses
Su	face Treatment:
Pas	ssivate
Su	face Treatment Specification:
Qq	p-35 federal specification single treatment response
Thr	ead Series Designator:
Und	
Spe	ecification Or Standard:
4 ty	pe
She	elf Life:
N/a	

## NSN 5305-01-194-4874

Socket Head Cap Screw - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0