

View Online at <https://aerobasegroup.com/nsn/5305-01-194-6148>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.908 inches and 1.000 inches

Fastener Length:

Between 0.970 inches and 1.000 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.306 inches and 0.322 inches

Head Height:

Between 0.105 inches and 0.115 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.164 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

55000 pounds per square inch

Product Name:

Navy special project

Screw Material:

Copper alloy 268 or copper alloy 260 or copper alloy 230 or copper alloy 377 or steel comp 4135h or copper alloy 353 or copper alloy 270 or copper alloy 274 or copper alloy 462 or copper alloy 464 or copper alloy 482 or copper alloy 485 or copper alloy 510 or copper alloy 745 or copper alloy 752 or copper alloy 757 or copper alloy 764 or copper alloy 770 or copper alloy 240 or copper alloy 342

Screw Material Specification:

Qq-b-613 federal specification 1st material response or qq-b-626 federal specification 2nd material response or qq-w-321 federal specification 3rd material response

Screw Surface Treatment Specification:

296-0052, type 4 fscm 49956 mfr ref single treatment response

Precious Material And Location:

silver and rhodium

Precious Material:

Silver and rhodium

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0