

View Online at <https://aerobasegroup.com/nsn/5305-01-194-7055>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.425 inches and 0.465 inches

**Fastener Length:**

Between 1.310 inches and 1.330 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.335 inches and 0.381 inches

**Grip Diameter:**

Between 0.1890 inches and 0.1895 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.865 inches and 0.885 inches

**Width Across Flats:**

Between 0.1253 inches and 0.1270 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Countersink Angle:**

100.0 degrees

**Surface Finish:**

32.0 microinches threads

**Special Features:**

Hole at threaded end reamed for press fit with plug

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5732 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0