

View Online at <https://aerobasegroup.com/nsn/5305-01-194-7055>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.425 inches and 0.465 inches

Fastener Length:

Between 1.310 inches and 1.330 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.335 inches and 0.381 inches

Grip Diameter:

Between 0.1890 inches and 0.1895 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.190 inches

Grip Length:

Between 0.865 inches and 0.885 inches

Width Across Flats:

Between 0.1253 inches and 0.1270 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Countersink Angle:

100.0 degrees

Surface Finish:

32.0 microinches threads

Special Features:

Hole at threaded end reamed for press fit with plug

Material:

Iron alloy 660

Material Specification:

Ams 5732 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0