NSN 5305-01-194-7059

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-194-7059

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.378 inches and 0.428 inches |
| Fastener Length: |
| Between 1.388 inches and 1.418 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.464 inches and 0.507 inches |
| Grip Diameter: |
| Between 0.2490 inches and 0.2495 inches |
| Internal Drive Style: |
| Offset cruciform (torque set) |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| Between 0.990 inches and 1.010 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Surface Finish: |
| 32.0 microinches threads |
| Special Features: |
| Internal drive ribbed |
| Material: |
| Titanium alloy |
| Material Specification: |
| Ams4967 assn standard single material response |
| |
| Thread Series Designator: |
| Thread Series Designator: Unif |
| Unjf |
| Unjf Specification Data: |
| Unjf |
| Unjf Specification Data: 80205-nas1580 professional/industrial association standard |
| Unjf Specification Data: 80205-nas1580 professional/industrial association standard Shelf Life: N/a |
| Unjf Specification Data: 80205-nas1580 professional/industrial association standard Shelf Life: |

NSN 5305-01-194-7059

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

