NSN 5305-01-194-8480



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-194-8480 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.256 inches and 0.296 inches **Fastener Length:** Between 1.206 inches and 1.226 inches **Head Style:** Flat chamfer **Head Diameter:** 0.375 inches **Head Height:** Between 0.190 inches and 0.210 inches **Shoulder Diameter:** 0.1998 inches first shoulder and 0.2000 inches first shoulder **Shank Unthreaded Hole Diameter:** 0.070 inches first hole and 0.080 inches first hole **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): Distance From Head Largest Bearing Surface To Shank Hole Center: 1.088 inches first hole and 1.118 inches first hole **Special Features:** Second shoulder tapered. Major diameter 0.200 in., tip diameter 0.190 in. Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Ps13001 fscm 76301 mfr ref single treatment response

Thread Series Designator: Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-194-8480

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0