NSN 5305-01-194-9178

Machine Screw - Page 1 of 2

A500d0



View Online at https://aerobasegroup.com/nsn/5305-01-194-9178

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.291 inches and 0.341 inches
Fastener Length:
Between 1.363 inches and 1.393 inches
Head Style:
Pan
Head Diameter:
Between 0.473 inches and 0.492 inches
Head Height:
Between 0.162 inches and 0.175 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
Between 36.0 rockwell c and 40.0 rockwell c
Screw Material:
Steel comp 4140 or steel comp e4340 or steel comp 8740
Screw Material Specification:
Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military
specification 3rd material response
Screw Surface Treatment:
Cadmium
Screw Surface Treatment Specification:
Qq-p-416, type 1 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:

NSN 5305-01-194-9178

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5626 spec.