## NSN 5305-01-195-5062

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-195-5062

Thread Cl	ass:
3a	
Thread Di	rection:
Right-hand	ł
Thread Le	ingth:
Between C	0.381 inches and 0.471 inches
Fastener	Length:
Between 1	.266 inches and 1.296 inches
Head Styl	e:
Flat counte	ersunk
Head Diar	neter:
Between C	0.338 inches and 0.381 inches
Grip Diam	leter:
Between C	0.1885 inches and 0.1895 inches
Internal D	rive Style:
High-torqu	e
Thread Di	ameter:
0.190 inch	es
Grip Leng	ith:
Between C	.865 inches and 0.885 inches
Thready Q	Qty Per Inch (tpi):
32	
Countersi	nk Angle:
Between 9	9.0 degrees and 101.0 degrees
Material:	
Steel com	o xm-13
Material S	pecification:
Ams 5629	assn standard single material response
Surface T	reatment:
Aluminum	
Surface T	reatment Specification:
Mil-c-8348	8 ty2 cl3 military specification single treatment response
Thread Se	eries Designator:
Unjf	
Shelf Life	:
N/a	
Unit Of M	easure:
Demilitari	zation:
No	
Fiig:	
A003b0	

NSN 5305-01-195-5062

Close Tolerance Screw - Page 2 of 2

Mil-std (military Standard):

Mil-c-83488 spec.

