

View Online at <https://aerobasegroup.com/nsn/5305-01-195-5807>

**Thread Direction:**

Right-hand

**Thread Length:**

Between 12.36 millimeters and 13.07 millimeters

**Fastener Length:**

Between 15.92 millimeters and 16.08 millimeters

**Head Style:**

Hexagon

**Head Height:**

Between 4.37 millimeters and 4.83 millimeters

**Width Between Flats:**

Between 9.78 millimeters and 10.00 millimeters

**Washer Quantity:**

1

**Internal Drive Style:**

W/o internal drive

**Thread Pitch In Millimeters:**

1.81

**Nonmachine Thread Style:**

Gimlet point (type a, ab or ba)

**Primary Washer Outside Diameter:**

Between 16.57 millimeters and 17.00 millimeters

**Primary Washer Style:**

Flat

**Primary Washer Material Thickness:**

Between 1.20 millimeters and 1.75 millimeters

**Nonmachine Thread Diameter:**

6.3 millimeters

**Material:**

Steel primary washer

**Material Specification:**

Gm 6010-m fscm 24617 mfr ref single material response

**Surface Treatment:**

Phosphate fastener

**Surface Treatment Specification:**

Gm 9093-p fscm 24617 mfr ref single treatment response fastener

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0