

View Online at <https://aerobasegroup.com/nsn/5305-01-195-5807>

Thread Direction:

Right-hand

Thread Length:

Between 12.36 millimeters and 13.07 millimeters

Fastener Length:

Between 15.92 millimeters and 16.08 millimeters

Head Style:

Hexagon

Head Height:

Between 4.37 millimeters and 4.83 millimeters

Width Between Flats:

Between 9.78 millimeters and 10.00 millimeters

Washer Quantity:

1

Internal Drive Style:

W/o internal drive

Thread Pitch In Millimeters:

1.81

Nonmachine Thread Style:

Gimlet point (type a, ab or ba)

Primary Washer Outside Diameter:

Between 16.57 millimeters and 17.00 millimeters

Primary Washer Style:

Flat

Primary Washer Material Thickness:

Between 1.20 millimeters and 1.75 millimeters

Nonmachine Thread Diameter:

6.3 millimeters

Material:

Steel primary washer

Material Specification:

Gm 6010-m fscm 24617 mfr ref single material response

Surface Treatment:

Phosphate fastener

Surface Treatment Specification:

Gm 9093-p fscm 24617 mfr ref single treatment response fastener

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0