NSN 5305-01-196-3858

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-196-3858 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.158 inches and 0.250 inches **Fastener Length:** Between 0.220 inches and 0.250 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.218 inches and 0.226 inches **Head Height:** Between 0.134 inches and 0.138 inches **Locking Feature:** Strip threads or patch threads or pellet threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.138 inches Width Across Flats: Between 0.109 inches and 0.111 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch **Product Name:** Navy special project **Special Features:** Color black Material: Steel **Surface Treatment:** Oxide **Surface Treatment Specification:**

Mil-c-13924, cl 1 military specification single treatment response

Thread Series Designator:

Unrc

NSN 5305-01-196-3858

Socket Head Cap Screw - Page 2 of 2



Specification D	ata:
-----------------	------

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.