## NSN 5305-01-196-3858

Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-196-3858



**Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.158 inches and 0.250 inches Fastener Length: Between 0.220 inches and 0.250 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.218 inches and 0.226 inches **Head Height:** Between 0.134 inches and 0.138 inches Locking Feature: Strip threads or patch threads or pellet threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.138 inches Width Across Flats: Between 0.109 inches and 0.111 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c **Minimum Yield Strength:** 155000 pounds per square inch **Product Name:** Navy special project **Special Features:** Color black Material: Steel **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924, cl 1 military specification single treatment response **Thread Series Designator:** 

Unrc

## NSN 5305-01-196-3858

Socket Head Cap Screw - Page 2 of 2



**Specification Data:** 

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

## Mil-std (military Standard):

Mil-c-13924 spec.