## NSN 5305-01-196-3859

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-196-3859 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.169 inches and 0.250 inches **Fastener Length:** Between 0.219 inches and 0.250 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.176 inches and 0.183 inches **Head Height:** Between 0.108 inches and 0.112 inches **Locking Feature:** Patch threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.112 inches Width Across Flats: Between 0.094 inches and 0.095 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 

Specificati 6 type Shelf Life: N/a

## NSN 5305-01-196-3859

Socket Head Cap Screw - Page 2 of 2



|    | • • |             |     |     |      |
|----|-----|-------------|-----|-----|------|
| In | 18  | <i>(</i> )+ | МЛО | 201 | ure: |
|    |     |             |     |     |      |

--

Demilitarization:

No

Fiig:

A003b0