## NSN 5305-01-196-5558



Machine Screw - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-01-196-5558 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.672 inches and 0.751 inches **Fastener Length:** Between 2.063 inches and 2.110 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.805 inches and 0.890 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.438 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 85000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 302b or steel comp 303 plus x or steel comp 303se or steel comp 303cu or steel comp 303ma or steel comp 304l **Screw Material Specification:** 66 federal standard all material responses **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

Fiig:

No

A500d0