Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-196-5571

view Online at https://aerobasegroup.com/nsn/5305-01-196-5571	
Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
2.000 inches	
Fastener Length:	
Between 3.170 inches and 3.250 inches	
Head Style:	
Flat chamfer	
Head Diameter:	
Between 1.107 inches and 1.125 inches	
Head Height:	
Between 0.740 inches and 0.750 inches	
Internal Drive Style:	
Hexagon	
Thread Diameter:	
0.750 inches	
Width Across Flats:	
Between 0.625 inches and 0.631 inches	
Thready Qty Per Inch (tpi):	
10	
Min. Tensile Strength (psi):	
70000 pounds per square inch	
Hardness Rating:	
74.0 rockwell b	
Minimum Yield Strength:	
26000 pounds per square inch	
Material:	
Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp xm-7 or steel comp 384	
Surface Treatment:	
Passivate	
Surface Treatment Specification:	
Qq-p-35 federal specification single treatment response	
Thread Series Designator:	
Unrc	
Specification Data:	
80205-nas1352 professional/industrial association standard	
Shelf Life:	
N/a	
Unit Of Measure:	

NSN 5305-01-196-5571

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

