NSN 5305-01-196-5577

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-196-5577 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.596 inches and 0.646 inches **Fastener Length:** Between 1.481 inches and 1.511 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.5149 inches and 0.5662 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.375 inches **Grip Length:** Between 0.865 inches and 0.885 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 class 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:**

Shelf Life:

N/a

80205-nas1581 professional/industrial association standard

NSN 5305-01-196-5577

Close Tolerance Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0