NSN 5305-01-197-1360



Externally Relieved Body Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-197-1360 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.407 inches and 0.469 inches **Fastener Length:** Between 0.844 inches and 0.875 inches **Head Style:** Binding **Head Diameter:** Between 0.380 inches and 0.390 inches **Head Height:** Between 0.112 inches and 0.123 inches **First Diameter From Head:** Between 0.148 inches and 0.155 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.375 inches and 0.468 inches **Point Style:** Flat **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Criticality Code Justification: Externally Relieved Body Diameter Quantity: Special Features:** Special binding head screw with undercut Material: Steel **Thread Series Designator: Reference Number Differentiating Characteristics:** As differentiated by packaging in accordance with mil-p-23199 and material conforming to ships parts control center special quality control provisions Shelf Life:

--

N/a

Unit Of Measure:

NSN 5305-01-197-1360

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0