

View Online at <https://aerobasegroup.com/nsn/5305-01-197-2530>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.355 inches and 1.500 inches

**Fastener Length:**

Between 1.438 inches and 1.500 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.340 inches and 0.385 inches

**Head Height:**

Between 0.240 inches and 0.385 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Countersink Angle:**

Between 80.0 degrees and 82.0 degrees

**Screw Material:**

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

**Screw Surface Treatment:**

Oxide

**Screw Surface Treatment Specification:**

Mil-c-13924 military specification single treatment response

**Color:**

Black

**Thread Series Designator:**

Unc

**Specification Or Standard:**

3 type and 2c style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0

**Mil-std (military Standard):**

Mil-c-13924 spec.