NSN 5305-01-197-3094

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-197-3094 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.171 inches **Fastener Length:** 0.562 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches **First Diameter From Head:** Between 0.095 inches and 0.105 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.391 inches **Point Style:** Flat **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 36.0 rockwell c and 40.0 rockwell c **Externally Relieved Body Diameter Quantity:** Material: Steel comp 4140 or steel comp e4340 or steel comp 8740 **Material Specification:** Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:**

Thread Series Designator:

Qq-p-416 type 2 class 1 federal specification single treatment response

Unc

NSN 5305-01-197-3094

Externally Relieved Body Screw - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):

Mil-s-5626 spec.