NSN 5305-01-197-3292



Thumbscrew - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-01-197-3292 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.490 inches and 0.510 inches **Head Style:** Knurled no. 4 **Head Diameter:** Between 0.490 inches and 0.510 inches Point Length: Between 0.115 inches and 0.135 inches **Point Diameter:** Between 0.123 inches and 0.124 inches **Point Style:** Chamfer dog **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 **Special Features:** Distance from top of head to beginning of threaded portion is 0.303 min. And 0.323 max. In. Material: Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385 **Material Specification:** Qq-s-763 federal specification all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig:

A003b0