Thumbscrew - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5305-01-197-3292

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.490 inches and 0.510 inches

Head Style:

Knurled no. 4

Head Diameter:

Between 0.490 inches and 0.510 inches

Point Length:

Between 0.115 inches and 0.135 inches

Point Diameter:

Between 0.123 inches and 0.124 inches

Point Style:

Chamfer dog

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

20

Special Features:

Distance from top of head to beginning of threaded portion is 0.303 min. And 0.323 max. In.

Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

Material Specification:

Qq-s-763 federal specification all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

