NSN 5305-01-197-3492



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-197-3492 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.130 inches **Fastener Length:** 0.292 inches **Head Style:** Hexagon **Head Height:** 0.075 inches Width Between Flats: 0.187 inches **Shoulder Diameter:** 0.123 inches first shoulder and 0.124 inches first shoulder **Shoulder Length:** 0.109 inches first shoulder and 0.115 inches first shoulder **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): 56 **Shoulder Shape:** Round first shoulder **Special Features:** Relief between threads and shoulder 0.050 length; 0.057 in. Min da, 0.063 in. Maximum dia Material: Steel comp 303se or steel comp 303 **Material Specification:** Astm-a582 assn standard all material responses or astm-581 assn standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Cps 130 fscm 04577 mfr ref single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-197-3492

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0