

View Online at <https://aerobasegroup.com/nsn/5305-01-197-3508>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.338 inches

**Fastener Length:**

Between 0.948 inches and 0.978 inches

**Head Style:**

Oval countersunk

**Head Diameter:**

Between 0.2966 inches and 0.3016 inches

**Grip Diameter:**

Between 0.1885 inches and 0.1895 inches

**Shank Unthreaded Hole Diameter:**

0.070 inches first hole and 0.080 inches first hole

**Internal Drive Style:**

Offset cruciform (torque set)

**Thread Diameter:**

0.190 inches

**Grip Length:**

0.625 inches

**Thready Qty Per Inch (tpi):**

32

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.822 inches first hole and 0.862 inches first hole

**Surface Finish:**

32.0 microinches threads

**Special Features:**

Dry film lubricant, internal drive ribbed

**Material:**

Titanium alloy

**Material Specification:**

Ams4967 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0