
## NSN 5305-01-197-3569

Close Tolerance Screw - Page 1 of 2





## **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.444 inches and 0.494 inches Fastener Length: Between 0.954 inches and 0.984 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.497 inches and 0.507 inches **Grip Diameter:** Between 0.2490 inches and 0.2495 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches Grip Length: Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi): 28 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Navy special project **Special Features:** Tapped hole in head 0.1380-32, unjc-3b threads. Distance from top of head to injection port 0.200 inch. Injection port 0.120 in. Lg, 0.060 in. Wide Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response Surface Treatment: Passivate **Thread Series Designator:** Unjf Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No

## NSN 5305-01-197-3569

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

