NSN 5305-01-197-4365

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-197-4365 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.160 inches and 0.190 inches **Fastener Length:** Between 0.395 inches and 0.425 inches **Head Style:** Flat countersunk **Head Diameter:** 0.231 inches **First Diameter From Head:** Between 0.074 inches and 0.078 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.220 inches and 0.250 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Color black Material: Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 **Material Specification:** Astm a493 assn standard all material responses **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-01-197-4365

Externally Relieved Body Screw - Page 2 of 2



Demi			

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.