

View Online at <https://aerobasegroup.com/nsn/5305-01-197-4647>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.334 inches and 1.500 inches

**Fastener Length:**

Between 1.438 inches and 1.500 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.226 inches and 0.243 inches

**Width Between Flats:**

Between 0.551 inches and 0.563 inches

**Shank Unthreaded Hole Diameter:**

0.105 inches first hole and 0.113 inches first hole

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

70000 pounds per square inch

**Hardness Rating:**

235.0 brinell standard

**Minimum Yield Strength:**

40000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.272 inches first hole and 1.354 inches first hole

**Material:**

Steel comp 410 or steel comp 416 or steel comp 430

**Material Specification:**

66 federal standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unf

**Specification Or Standard:**

2 type and 10p style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0